

Replacement coil, Tool-less plug connection, 230 V 50 Hz, 240 V 60 Hz, AC,
For use with: DILM17, DILM25, DILM32, DILM38, DILMP32 - DILMP45

Part no. DILM32-XSP(230V50HZ,240V60HZ)
Catalog No. 281141
Alternate Catalog XTCERENCOILCF
No.
EL-Nummer 4130502
(Norway)

Delivery program

Actuating voltage			230 V 50 Hz, 240 V 60 Hz
Voltage AC/DC			AC
For use with			DILM17 DILM25 DILM32 DILM38 DILMP32 - DILMP45
For use with			DILM17 - DILM38

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ		V	230 - 230
Rated control supply voltage Us at AC 60HZ		V	240 - 240
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC