## Technical data and compliance with Standards

| ELECTRICAL AND MECHANICAL CHARACTERISTIC | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Rated current In (A) | Degree of protection (IP) | Standard* | Rated voltage Un (V) | Permissible overload (A) | No. of operations carried out | Breaking capacity at 1.1 Un (A) | Impact resistance (IK) | Insulation resistance (MΩ) | Heat resistance | Resistance to abnormal heat and fire |
| | | | | | | | | | Thermo-pressure with ball (°C) | Glow Wire Test (°C) |
| 16 | IP44 e IP67 | EN 60309-1 (CEI 23-12/1) EN 60309-2 (CEI 23-12/2) | Da 24 a 500 | 22 | > 5000 | 20 | IK 08 | > 10 | 125 Passive parts 80 Active parts | 850 Active parts 650 Passive parts |
| 32 | | | | 42 | > 2000 | 40 | | | | |
| 63 | | | | - | > 2000 | 79 | | | | |

*When applicable.

| BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Saline solution | Acids | | Bases | | Solvents | | | | Mineral oil | UV rays |
| | Concentrated | Diluted | Concentrated | Diluted | Hexane | Benzol | Acetone | Alcohol | | |
| Resistant | Not resistant | Limited resistance | Limited resistance | Resistant | Resistant | Resistant | Resistant | Resistant | Resistant | Resistant |

## Dimension tables - Multiple and adptor socket-outlets

### MOBILE WATERTIGHT MULTIPLIERS - IP67




| CODE | A | B | C | No. OUTPUTS |
|---|---|---|---|---|
| GW 64 008 | | 146 | 235 | |
| GW 64 010 | | | | |
| GW 64 009 | | 156 | 246 | 2 |
| GW 64 011 | | | | |
| GW 64 012 | | 166 | 258 | |
| GW 64 014 | | | | |
| GW 64 022 | 218 | | 235 | |
| GW 64 024 | | | | |
| GW 64 023 | | | | 3 |
| GW 64 025 | 230 | | 246 | |
| GW 64 027 | | | | |

| CODE | A | C | No. OUTPUTS |
|---|---|---|---|
| GW 64 026 | 242 | 258 | |
| GW 64 028 | | | |
| GW 64 059 | 245 | 260 | |
| GW 64 060 | | | |
| GW 64 062 | 235 | 265 | |
| GW 64 063 | 250 | 280 | |
| GW 64 064 | 255 | 295 | 3 |
| GW 64 061 | 280 | 305 | |
| GW 64 065 | 295 | 370 | |
| GW 64 068 | 270 | 270 | |

### MOBILE MULTIPLIERS WITH WATERTIGHT CABLE AND PLUG - IP67




| CODE | A | B |
|---|---|---|
| GW 64 050 | 218 | 254 |
| GW 64 052 | | |
| GW 64 051 | 230 | 262 |
| GW 64 053 | | |
| GW 64 055 | | |
| GW 64 054 | 242 | 277 |
| GW 64 056 | | |

### PROTECTED MOBILE PHASE INVERTER ADAPTERS




| CODE | A | B |
|---|---|---|
| GW 64 066 | 76 | 196 |
| GW 64 067 | 83 | 196 |

### MOBILE SYSTEM ADAPTERS (FROM INDUSTRIAL TO DOMESTIC)




| CODE | A |
|---|---|
| GW 64 203 | |
| GW 64 204 | |
| GW 64 206 | |
| GW 64 210 | 118 |
| GW 64 211 | |
| GW 64 212 | |
| GW 64 215 | |
| GW 64 207 | |
| GW 64 216 | 123 |
| GW 64 217 | |

### MOBILE SYSTEM ADAPTERS (FROM DOMESTIC TO INDUSTRIAL)




GW 64 208




GW 64 209

For technical information contact the Technical Assistance Service or visit gewiss.com

## MOBILE SYSTEM ADAPTER SHUNTS WITH PLUG




| CODE | A | B | C | No. OUTPUTS |
|---|---|---|---|---|
| GW 64 221 | | 125 | 233 | 2 |
| GW 64 222 | | | | |
| GW 64 223 | | | | |
| GW 64 226 | | 134 | 245 | |
| GW 64 227 | | | | |
| GW 64 228 | | | | |
| GW 64 231 | 194 | | 233 | 3 |
| GW 64 232 | | | | |
| GW 64 236 | 202 | | 245 | |
| GW 64 237 | | | | |

## MOBILE SYSTEM ADAPTER SHUNTS WITH CABLE AND PLUG




| CODE | A | B |
|---|---|---|
| GW 64 263 | 194 | 242 |
| GW 64 265 | | |
| GW 64 256 | 202 | 254 |