



# Ledinaire floodlights gen3

## BVP165 LED120/840 PSU 100W SWB CE

- - 840 neutral white - - - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

### Product data

General information		Number of products on MCB of 16 A type B	
Lamp family code	-		22
Light source color	840 neutral white	Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Light source replaceable	No	Photobiological risk specification	0.2 m
Number of gear units	1 unit	EU RoHS compliant	Yes
Driver/power unit/transformer	-	Light source engine type	LED
Driver included	Yes	Service tag	No
Optical cover/lens type	Glass	Light technical	
Luminaire light beam spread	110° x 110°	Upward light output ratio	0
Control interface	-	Standard tilt angle posttop	-
Connection	Flying leads/wires	Standard tilt angle side entry	-
Cable	Cable 2.0 m without plug	Operating and electrical	
Protection class IEC	Safety class I	Input Voltage	220 to 240 V
Flammability mark	-	Input Frequency	50 or 60 Hz
CE mark	CE mark	Initial CLO power consumption	- W
ENEC mark	-	Average CLO power consumption	100 W
Warranty period	3 years	End CLO power consumption	- W
Optic type outdoor	Symmetrical		
Constant light output	No		

## Ledinaire floodlights gen3

Inrush current	3.84 A
Inrush time	0.0244 ms
Power Factor (Min)	0.95

### Controls and dimming

Dimmable	No
----------	----

### Mechanical and housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	220 mm
Overall width	312 mm
Overall height	32.5 mm
Effective projected area	0.045 m <sup>2</sup>
Color	Gray
Dimensions (Height x Width x Depth)	33 x 312 x 220 mm

### Approval and application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]
Surge Protection (Common/Differential)	4/4 kV
Sustainability rating	-

### Initial performance (IEC compliant)

Initial luminous flux (system flux)	12000 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	100 W
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

### Over time performance (IEC compliant)

Control gear failure rate at median useful life	5 %
50000 h	
Lumen maintenance at median useful life*	80
50000 h	

### Application conditions


Ambient temperature range	-25 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

### Product data

Full product code	871951453351699
Order product name	BVP165 LED120/840 PSU 100W SWB CE
CE	
EAN/UPC - Product	8719514533516
Order code	53351699
Local order code	BVP165L1284UISC
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	911401856483
Net Weight (Piece)	1.760 kg



## Dimensional drawing



BVP165 LED120/840 PSU 100W SWB CE

## Ledinaire floodlights gen3

