


Flush-mounting axial auxiliary module with two commands. Two axial push-buttons on the front; this product can be used in combination with the auxiliary wired inputs of the following devices of the Chorusmart range: connected commands, connected 1- channel On/Off actuator, connected movement sensors, EVO commands, or as a wired command for a connected 2-channel ZigBee interface. The device must be completed with one of the front buttons key available.

Descriere	2-channel auxiliary axial control	Contacte de ieșire	n. 2 x 1A (AC1)
Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Nr. module	2
Nr. canale în ieșire	2	Standard	2014/35/EU (LVD), 2011/65/EU + 2015/863 (RoHS), EN 60669-1, EN IEC 63000
Temperatură de funcționare	-5 ÷ +45 °C	Relative humidity (non-condensative)	Max 93%
Terminale de cablare	Cu șuruburi	Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5
Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5	Categorie	2-channel auxiliary axial control
Nr. canale în intrare	-	Clasă de protecție IP	IP20 (with button key)
240 V ac Incandescent-halogen lamps	-	240 V ac LED lamps	-
Loads piloted from electronic transformers 240 V ac	-	LED colour	Albastru
Local control	Via 2 front push buttons (to complete with button key)	Load control	-
Material	Tehnopolimer		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS

