




Wide range of control devices, sockets for power supply (conforming to national and international standards) signal pick-up, climate control, comfort management, technical alarm signalling and emergency lighting management. The ChoruSmart modular devices are available in five colours, glossy white, satin white, natural beige, satin black and lacquered titanium and in various sizes from 1/2, 1, 2 and 3 modules. Thanks to the mounting supports for rectangular, square and round boxes, endless combinations can be created with the ChoruSmart range of plates.

Categorie	Senzor de micare	Contacte de ieşire	1NO 3 A (AC1) 230 V ac
Material	Tehnopolimer	Culoare	Satin White
Tensiune de alimentare	230V ac - 50/60 Hz	Tehnologie	Infraroşii
Standard	EN 60669-1, EN 60669-2-1	Rezistenţă la tensiunea de test	2000 V la 50 Hz pentru 1 minut
Rezistenţa izolaţiei	> 5 MOhm	Terminale de cablare	Cu şuruburi
Funcţionare prelungită (nr. de schimbări de poziţie)	40.000 la In 250 V ac cosφ=0,6	Termo-presiune cu bilă	125 °C
Glow Test conductori	850 °C	Strângere terminal la tracţiune cablu	> 50 N
Capacitate strângere terminal cabluri flexibile (mm²)	min. 0,75 - max. 2x4	Capacitate strângere terminal cabluri rigide (mm²)	min. 0,5 - max. 2x2,5
Nr. module	1	Electrocod	0513

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

