


Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Culoare	Negru satinat	Contacte de ieşire	1 NA 2 A (AC1) 240 Vac
Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Nr. module	1
Nr. canale în ieşire	1	Radio connections	Zigbee (IEEE 802.15.4)
Standard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000	Temperatură de funcţionare	-5 ÷ +45 °C
Relative humidity (non-condensative)	Max 93%	Power output Zigbee	10 dBm
Terminale de cablare	Cu şuruburi	Capacitate strângere terminal cabluri flexibile (mm ²)	Max. 1,5
Capacitate strângere terminal cabluri rigide (mm ²)	Max. 1,5	Categorie	Senzor de micare
Nr. canale în intrare	2 (for local command replication or sending additional Zigbee commands)	Tensiune de intrare	Mains supply voltage
Clasă de protecţie IP	IP20	240 V ac Incandescent-halogen lamps	500W
240 V ac LED lamps	100 W	Loads piloted from electronic transformers 240 V ac	250 VA
Tehnologie	Infraroşii	Senzor luminozitate	1-600 lux
Horizontal bearing angle	±48°	Vertical bearing angle	±10°

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS

UK CA

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 29/03/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice