




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

| | | | |
|---|--|--|------------------------|
| Culoare | Natural satin beige | Contacte de ieșire | 1 NA 2 A (AC1) 240 Vac |
| Sursă de alimentare | 100 ÷ 240 V ac - 50/60 Hz | Nr. module | 1 |
| Nr. canale în ieșire | 1 | Radio connections | Zigbee (IEEE 802.15.4) |
| Standard | 2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000 | Temperatură de funcționare | -5 ÷ +45 °C |
| Relative humidity (non-condensative) | Max 93% | Power output Zigbee | 10 dBm |
| Terminale de cablare | Cu șuruburi | Capacitate strângere terminal cabluri flexibile (mm ²) | Max. 1,5 |
| Capacitate strângere terminal cabluri rigide (mm ²) | Max. 1,5 | Categorie | Senzor de micare |
| Nr. canale în intrare | 2 (for local command replication or sending additional Zigbee commands) | Tensiune de intrare | Mains supply voltage |
| 240 V ac Incandescent-halogen lamps | 500W | 240 V ac LED lamps | 100 W |
| Loads piloted from electronic transformers 240 V ac | 250 VA | Tehnologie | Infraroșii |
| Senzor luminozitate | 1-600 lux | Horizontal bearing angle | ±48° |
| Vertical bearing angle | ±10° | | |

DIMENSIONAL



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 29/03/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice