




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Sursă de alimentare	100 ÷ 240 V ac - 50/60 Hz	Nr. canale	2
Nr. module	1	Radio connections	Zigbee (IEEE 802.15.4)
Standard	-	Temperatură de funcționare	-5 ÷ +45 °C
Relative humidity (non-condensative)	Max 93%	Power output Zigbee	10 dBm
Terminale de cablare	Cu șuruburi	Capacitate strângere terminal cabluri flexibile (mm²)	Max. 1,5
Capacitate strângere terminal cabluri rigide (mm²)	Max. 1,5	Categorie	2-channel push-button control panel
Nr. canale în intrare	2 (for local command replication or sending additional Zigbee commands)	Tensiune de intrare	Mains supply voltage
Clasă de protecție IP	IP20 (with button key)	LED colour	Albastru
Local control	Via 2 front push buttons (to complete with button key)	Power supply of EGO SMART plate	Da
Zigbee control extension if installed in an EGO SMART plate (SHIFT function)	Yes (2 Zigbee command activated with front push buttons)		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS

