



The floor-standing I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market able to guarantee the IP55 level of protection. The special hexagonal design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the User Experience for the Driver. They are available with standard JoinOn graphics, which may be customised on request.

<b>INPUT</b>		- Socket/Connector Nr. (Type)	2 (Type 2 vandal-proof socket, with shutters)
Terminal blocks	5 x 35 mm <sup>2</sup>	Charging activation	Locally managed, via RFID
Current nominal	64 A	Human Interface	LED RGB and TFT Display
Total power	44 Kilowatt	Connectivity	Nu
<b>OUTPUT</b>		<b>MECHANICAL FACTS</b>	
Tensiune nominală	400 V	Mounting and installation	Floor mounting
Current alimentat (max)	32 A per socket	Culoare	Grey, Headboard RAL 7011
Putere max.	22 kW per socket	Material	Steel sheet
Thermal-magnetic protection	40A - 4P - D Curve	External treatments	Anti-corrosion and anti-graffiti
Tip de protecție diferențială	40 A - 4P - Type B	Clasă de protecție IP	IP55
Contor energie	Yes (Type MID)	Cod IK	IK10
DC Leakage check	Not needed	Temperatură de operare	-25 +50 °C
(Auto)restart electrical protections	Nu	Customizations	Yes (front)

## DIMENSIONAL



## TECHNICAL SYMBOLOGY

**IP**

IP55

**IK**

IK10

## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 23/08/2023

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice